



KANGAROO

ACRYLIC

SPRAY PAINT



- Ozone-friendly
- Protects & Beautifies
- Quick-drying
- Easy to use
- Interior & Exterior
- Non-toxic
- Superior Quality
- Washable
- Fashionable Colors
- Excellent Gloss & Color Retention



KANGAROO


NON METALLIC




Bright Yellow 32



Ivory 21




Light Grey 19




Olympic Blue 38



Lemon 07



Baltic White 156




Rhino Grey 191




Nissan Blue 39



Yellow 30




Silver Mist 42




Honda Grey 128




Sea Blue 137




Orange 14



Fuschia 134



Petronas Green 62



Riviera Blue 44



Paprika 23



Anti-Rust Primer 69



Fresh Green 15



Oxford Blue 61



Vermillion Red 52



Pelandok 13



Flash Green 118



Purple 27



Fast Red 12



Signal Red 10



Pine Green 17

Also available in 20 clear, 02 White, 03 Black and 09 Flat Black.

ACRYLIC SPRAY PAINT

METALLIC COLOURS




Champagne 783



Royal Blue 71



Pacific Blue 83




Silver 68



Beige Metallic 731




Green Pearl 715



Honda Blue 82



Sparkle Silver 700



Brilliant Gold 777



Supreme Green 730



Yamaha Blue 73



Gerhana Grey 88



Solid Gold 77



Sunset Red 705



Blue Met 716



Metallic Black 89



Purple 712



Carmine Red 708



Shimmer Blue 719

CANDY TONE



Candy Undercoat 90



Rubine Red 91



Caribbean Blue 93



KANGAROO ACRYLIC SPRAY PAINT



- **DIRECTIONS FOR USE :**

Shake can thoroughly until metal agitator moves freely for least 30 seconds. Remove plastic cap. Hold container approximately 30 cm from article to be sprayed; point spray head opening towards objects to be sprayed; hold can vertically, depress spray valve with forefinger and move spray can back and forth so that an even film of paint is deposited on the surfaces. Several thin coats allowing each coat to dry for at least 10 minutes, are better than one thick coat.

- **CAUTION:**

Do not spray near fire or open flame. Store can below 40°C. Spray in a well ventilated area. Surfaces to be sprayed should be free from dirt, rust, grease, etc.

- **PERATURAN :**

Goncang tin/botol sekurang-kurangnya 30 saat sehingga besi pembancur bergerak. Buka tudung plastik, pegang tin/botol sekurang-kurangnya 12-14 inci dari barang yang hendak disemur, halakan lubang kepala penyembur kepada barang yang hendak disemur, pegang tin/botol menegak ke atas, tekankan valve penyembur dengan jari telunjuk dan gerakkan penyembur pergi dan balik supaya dapat lapisan cat yang licin dan nipis.

- **PERHATIAN:**


Jangan sembur berhampiran api. Simpan di tempat yang sejuk di bawah paras 40°C. Jangan menempatkan barang berat di atas tin. Sebelum penyembur tin harus digoncang selama 30-60 saat. Permukaan yang hendak disemur haruslah licin dan bersih.

- **用法：**

施法时，先摇动喷漆罐约30秒钟至漆混合均匀。然后在距离被喷物约30cm处，用食指压下喷头，来回摆动以得均匀表明。采用多次喷法，每隔10分钟喷上薄薄一层，效果会比一次完成更佳。

- **注意：**

使用喷漆时应远离火源，在空气流通处喷。收藏於低温处（40°C以下）。施工之物面须保持清洁而无油污及蜡质。



MANUFACTURED BY:
CHIN WAH (PAINTS) PTE LTD
KANGAROO PAINT MFG. SDN BHD (186857-U)

