



NU-COTE WATERLAC

Water-Based Transparent Finish



Water-Based
Low VOC
Formaldehyde Free
Heavy-Metals Free
APEO Free

NU-COTE WATERLAC

Premium transparent semi-gloss finish (water-based)	
Standard Packing	1L & 5L
Colour	As per colour chart
Application	Exterior/ Interior
For use on	Wood/ timber
• Pure acrylic formulation • Low VOC & reduced odour • Fast drying • Moisture tolerant	

NU-COTE WATERLAC

Nu-Cote WaterLac is a high quality 100% acrylic water-based transparent semi-gloss finish with good abrasion resistant property. It is most suitable on new parquet floors, wooden furniture, wood paneling and wooden doors. This **water-based** product features **low VOC**, **formaldehyde free**, **heavy-metals free** and **APEO free**, formulated with great care for your ease of mind when considering its effect to your health and the environment.

Colour	Clear Glossy and Coloured (See Nu-Cote Transparent Timber Series Colour Card)	
Pack Size	1 and 5 litres	
Composition	<i>Binder</i>	Pure acrylic emulsion
	<i>Pigment</i>	Pigment preparations
	<i>Solvent</i>	Water
Volume Solid	Average 40 ± 2%, varying with colours	
Recommended Dry Film thickness	30 – 50 microns (per coat)	
Drying Times *	<i>Touch Dry</i>	Within 1 hour
	<i>Hard Dry</i>	Within 2 hours
Full Cure *	3 – 4 weeks; Time for the coating to reach its full chemical/mechanical properties and will resist and perform as per the properties featured	
Over-coating Interval *	Minimum 3 hours	
Spreading Rate *	8 – 13 m ² /litre/coat (varies with roughness and porosity of substrate)	
Application	<i>Brush/Roller</i>	Use as is, thin not exceeding 5% by volume with water if necessary
	<i>Conventional Spray</i>	Thin with water to 20% by volume
	<i>Airless Spray</i>	Thin with water to 10% by volume
Surface Preparation	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
<i>Wood/Timber</i>	- Ensure surface free from oil, grease and other contaminant - Sand surface with abrasive paper for better adhesion and appearance	- Remove loose adhering paint - Ensure surface is clean and dry
Recommended No. of Coat	2 to 3 coats	

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd.** Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **6 NOV 2023**

<end of document>

TRANS[®]
PAINT

Nu-Cote[®] **TRANSPARENT WOOD SERIES**

Nu-Cote[®]
WATERLAC



- Glossy
- Pure acrylic water-based finish
- Quick-dry, low VOC & reduced odour
- Moisture tolerant
- Lead, Mercury, Formaldehyde & APEO Free
- For interior and limited exterior Use

- High Gloss
- Polyurethane alkyd Solvent-based finish
- Excellent abrasion resistance and durability
- Good tolerance towards alkalinity
- For interior use



Nu-Cote[®]
TIMBER

Note : Colours achieved may vary on different types / colours of wood surfaces.

注：在书上的色彩只供参考，色彩将视所用之木材种类/颜色而定。

Nota : Warna yang dihasilkan mungkin berbeza pada permukaan kayu yang berlainan jenis / warna.

Three coats are recommended for best finish.

建议髹三层以达到最好的效果。

**NU-COTE WATERLAC
(SATIN)**

**NU-COTE TIMBER
(GLOSSY)**

**NU-COTE WATERLAC
(SATIN)**

**NU-COTE TIMBER
(GLOSSY)**



700W

Clear

700



707W

Plum Shadow

707



701W

Sundance

701



708W

Anise Brown

708



702W

Poppy Love

702



709W

Ancient Cave

709



706W

Kurma Brown

706



710W

Black

710

TRANS PAINT COATINGS SDN. BHD. (Co. No. 197801000459)

Factory :

Lot 1393, Jalan Meranti, Bintawa Industrial Estate,
93450 Kuching, Sarawak, Malaysia.

Tel: 6082 334 222/ 6082 334 222

Fax: 6082 339 189

Registered Office (GST ID No.: 0000 4888 9856) :

Wisma Hii Yii Ngiik, 1st Floor, Lot 7573, Jalan Kwong Lee Bank,
93450 Kuching, Sarawak, Malaysia.

Tel: 6082 339 993

Fax: 6082 483 177



Certificate No.0402974