



PLUS AP SEALER SV

Premium Solvent Wall Sealer



PLUSS AP SEALER SV



Premium exterior/ interior wall sealer (solvent-based)	
Standard Packing	5L
Colour	White only
Application	Exterior and Interior
For use on	Concrete/ masonry Wood/ timber Iron/ steel
• Solvent based acrylic primer – excellent chemical and alkaline resistance • Excellent adhesion - suitable for chalky surfaces and previously painted substrate • Extremely high opacity - obliterates substrate allowing two-coat finish • Multipurpose and recoatable with all systems - use under water or oil based finishes, one product primes, seals and undercoats	

PLUSS ADHESION PROMOTING (AP) SEALER SV

This is a solvent-based sealer specially formulated for any masonry surfaces where excellent adhesion and alkaline resisting properties are required for lasting protection. It can be used with minimal surface preparation for all weather application.

Colour	White	
Pack Size	5, 18 litres	
Composition	<i>Binder</i>	Thermoplastic acrylic resin
	<i>Pigment</i>	Inorganic and mineral pigments
	<i>Solvent</i>	Hydrocarbon mixture
Volume Solid	51 ± 2%	
Recommended Dry Film thickness	30 – 40 microns (per coat)	
Drying Times *	<i>Touch Dry</i>	Within 30 minutes
	<i>Hard Dry</i>	Within 2 hour
Full Cure *	3 – 4 weeks; Time for the coating to reach its full chemical/mechanical properties and will resist and perform as per the properties featured	
Over-coating Interval *	Minimum 2 hours	
Spreading Rate *	8 – 12 m ² /litre/coat	
Application	<i>Brush/Roller</i>	Use as is, thin not exceeding 5% by volume with paint thinner if necessary
	<i>Conventional Spray</i>	
	<i>Airless Spray</i>	
Surface Preparation	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
	Ensure concrete substrate is cured (moisture content not more than 17% and pH not more than 9)	- Remove visible flakes or peels - Wash surface
Recommended Painting System	<u><i>Sequence</i></u>	<u><i>Product</i></u>
	Primer (1 coat) Finish (2 coats)	PLUSS AP SEALER SV NU-COTE WEATHER, NU-COTE RICH, NU-COTE EMULSION, NU-COTE OCEANGLO

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **20 JUL 2023**

<end of document>