

Immerse In The
High-Gloss Enamel

TRANS
PAINT

www.transpaint.yungkong.com



TOP
Cat Kilat



UNDERCOAT



TOP CAT KILAT UNDERCOAT

Interior gloss undercoat (solvent-based)

Standard Packing	1L, 5L & 18L
Colour	White only
Application	Interior only
For use on	Wood/ timber Iron/ steel
• Cost-effective application • Good build • Quick drying – saves time for recoating • Excellent filling and flow for a smooth finish	

TOP CAT KILAT UNDERCOAT

This is an economical and good build undercoat for exterior and interior use on wooden and metallic surfaces.

Colour	White	
Pack Size	1, 5 and 18 litres	
Composition	<i>Binder</i>	Oil-modified alkyd
	<i>Pigment</i>	Titanium dioxide and mineral extenders
	<i>Solvent</i>	Hydrocarbon mixture
Volume Solid	57 ± 2%	
Recommended Dry Film thickness	30 – 40 microns (per coat)	
Drying Times *	<i>Touch Dry</i>	Within 1 hour
	<i>Hard Dry</i>	Within 2 hours
Full Cure *	3 – 4 weeks; Time for the coating to reach its full chemical/mechanical properties and will resist and perform as per the properties featured	
Over-coating Interval *	Minimum 6 hours	
Spreading Rate *	13 – 17 m ² /litre/coat	
Application	<i>Brush/Roller</i>	Use as is, thin not exceeding 5% by volume with paint thinner or white spirit/mineral turpentine if necessary
	<i>Conventional Spray</i>	Thin with paint thinner or white spirit/mineral turpentine to 20% by volume
	<i>Airless Spray</i>	Use as is
Surface Preparation	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
<i>Metal/Mild Steel</i>	- Remove rust or mill scales by manual or mechanical cleaning - Ensure surface free from oil, grease and other contaminant	- Remove loose adhering paint - Remove debris, oil, grease or other contaminant before painting - Use suitable primer
<i>Wood/Timber</i>	- Ensure surface free from oil, grease and other contaminant - Sand surface with abrasive paper for better adhesion and appearance	- Remove loose adhering paint - Ensure surface is clean and dry - Use suitable primer
Recommended Painting System	<u><i>Sequence</i></u>	<u><i>Product</i></u>
<i>Metal/Mild Steel</i>	Primer (1 coat) Undercoat (1 coat) Finish (2 coats)	TOP GREYGREEN OXIDE 437 TOP CAT KILAT UNDERCOAT TOP CAT KILAT
<i>Wood/Timber</i>	Undercoat (1 coat) Finish (2 coats)	TOP CAT KILAT UNDERCOAT TOP CAT KILAT

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **20 JUL 2023**

<end of document>