

PAINT YOUR WORLD WITH

Luxurious Colours

TRANS
PAINT

www.transpaint.yundoo.com

ecLITE
Emulsion Paint



ECLITE EMULSION



Water-Based
Low VOC
Heavy-Metals Free

Economical interior wall matt finish (water-based)

Standard Packing

7L

Colour

As per colour chart

Application

Interior only

For use on

Concrete/ masonry

- Matt water based finish - minimizes surface irregularities
- Offers more factory packaged colours than that of competitors'
- Extremely cost effective application with considerable good paint film properties
- Good tolerance towards normal interior atmospheric humidity
- Ease of application - same day recoat, easy clean up and low odour

ECLITE EMULSION

This is a cost-effective emulsion paint specially formulated for interior walls. It gives a very comfortable and non-reflective appearance and has strong resistance against algae and fungus. This **water-based** product features **low VOC** and **heavy-metals free**, formulated with great care for your ease of mind when considering its effect to your health and the environment.

Colour	White	
Pack Size	7 and 18 litres	
Composition	<i>Binder</i>	Vinyl acetate/acrylic ester copolymer emulsion
	<i>Pigment</i>	Inorganic, organic pigments and mineral extenders
	<i>Solvent</i>	Water
Volume Solid	36 ± 2%	
Recommended Dry Film thickness	30 – 50 microns (per coat)	
Drying Times *	<i>Touch dry</i>	Within 30 minutes
	<i>Hard Dry</i>	Within 1 hour
Full Cure *	3 – 4 weeks; Time for the coating to reach its full chemical/mechanical properties and will resist and perform as per the properties featured	
Over-coating Interval *	2 hours minimum	
Spreading Rate *	7 – 11 m ² /litre/coat	
Application	<i>Brush/Roller</i>	Use as is, thin not exceeding 5% by volume with water if necessary
	<i>Conventional Spray</i>	Thin with water to 20% by volume
	<i>Airless Spray</i>	Thin with water to 10% by volume
Surface Preparation	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
	- Ensure surface is clean and dry - Apply appropriate sealer	- Remove loose paint film by hard scraping/high pressure water jet - Treat fungi, algae or mould with fungicidal wash - Ensure dry off before painting
Recommended Painting System	<u><i>Sequence</i></u>	<u><i>Product</i></u>
	Primer/Undercoat (1 coat) Finish (2 coats)	ECLITE SEALER/ECLITE UNDERCOAT ECLITE EMULSION

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **6 NOV 2023**

<end of document>

eCLITE®

Emulsion Paint




For a colourful life

ecLITE[®]

Emulsion Paint

For a colourful life



Elegant White 9101



Easy 7224



Engage 7003




Endeavor 7655



Esprit 7792



Eelgrass ★ 7433



Edge ★ 7357



Expression 7515



Elite 7719




Enjoy 7374



Era ★ 7729



Elephant 7868



Equator 7828



Estate ★ 7404




Exotic 7826



E-Blue 7772



Ebullient 7847



Eon ★ 7373



Effect ★ 7749



Empire 7876




Energy ★ 7455



Element ★ 7813



Excel ★ 7934




Euphrates ★ 7886

Also available in 9102 WHITE, 9103 BLACK & 9104 (P) BLACK

★ Premium Colours




Enchant 7128



Escapade 7297



Easter 7312



Eiffel 7611



Elixir 7180



Ember ★ 7343



Extreme 7319



Endure 7948



Espresso 7229




Excite ★ 7145



Elevate ★ 7571



Excalibur 7881



Éclair 7381




Esteem 7679




Eldorado ★ 7335



Elation 7690



Ebony ★ 7387



Entice ★ 7698



Eagle 7023




Elf 7393



Electra ★ 7744



Euphoria ★ 7702



Elkhorn ★ 7855



Eccentric 7288



INTERIOR



ROLL ON



BRUSH ON



SPRAY ON

MIN 2 HRS
RECOAT

ecLITE cat emulsi adalah diformulasi khas untuk kegunaan dinding dalaman bagi permukaan simen, siling, asbestos, kayu dan sebagainya. Ia memberi permukaan yang selesa dan tidak pantuk cahaya. Di samping itu, ia juga dapat mencegah pertumbuhan alga dan fungi. Harga ecLITE cat emulsi adalah berpatutan dan merupakan produk yang berbaloi dibeli.

Cara Penggunaan

Kacau sebatu sebelum menggunakannya. Untuk hasil yang terbaik, adalah tidak perlu untuk mencairkan cat. Campur hanya dengan 10% air jika diperlukan.

Untuk permukaan yang baru, biar permukaan kering sepenuhnya selama 3 minggu dan pastikan permukaan adalah bersih dan bebas daripada gris, minyak dan kotoran lain. Untuk permukaan dinding yang dicat sebelumnya, pastikan tiada pertumbuhan fungi, alga dan cat longgar pada permukaan. Untuk hasil yang lebih baik, catkan 1 lapis cat alas anti-alkali sebelum mengecat cat kemas.

Untuk hasil yang lebih memuaskan, cat 2-3 lapisan cat kemas dengan selang masa antara lapisan sekurang-kurangnya 2 jam.

ecLITE emulsion paint is specifically formulated for interior walls; it is suitable to paint on concrete, ceiling, asbestos, wood, etc. It gives a very comfortable and nonreflective surface, besides it also has strong resistance against algae and fungus. ecLITE emulsion paint is a cost-effective and value worth product.

Directions For Use

Stir well before use. For best result, thinning is not required. If necessary, thin with water to 10% by volume.

For fresh walls, let the surface dry thoroughly for at least 3 weeks and ensure the surface is clean, free from grease, oil and other contaminants before painting. For previously painted surface, ensure the surface has no fungus stain, algae growth and no loose paint film. For better painting result, apply 1 coat of alkali resistant sealer before applying finishing coats.

To get a more satisfactory outcome, apply 2-3 coats finishing paint with at least 2 hours recoating interval.



ecLITE是经过专门研制而成的室内乳胶漆，它适用于混凝土，天花板，石棉，木材等，给人一种非常舒适且不反光的高雅表面，此外它还具有对抗藻类和真菌的功能。ecLITE乳胶漆是货真价实，经济实惠，值得购买的产品。

用法

使用前请搅拌均匀。为了达到最好的效果，避免将漆稀释。若有必要，可加入百分之十的水份。

新的墙壁应让表面彻底干燥至少三周，并确保表面清洁，无油脂、油和其他污染物方可上漆。已上过漆的墙壁，确保表面没有藻类的生长也没有松动的漆膜。若要达到更好的效果，可先漆上一层耐酸碱底漆后才上面漆。

若要达到好的效果，可重复漆上2-3次，重涂间隔至少2个小时。



Trans Paint Coatings Sdn. Bhd. (197801000459)
Lot 1393, Jalan Meranti, Bintawa Industrial Estate,
93450 Kuching, Sarawak, East Malaysia.
Tel. 6082-334 222/ 6082-334 166, Fax. 6082-339 189
www.transpaint.yungkong.com



Certificate No.0402974